

MTD Series Modular Chillers

Engineered for Environmentally Safe R-410A Refrigerant



The Cruisair MTD is a modular chiller engineered for optimal use of the new environmentally safe R-410A refrigerant. This tempered-water unit provides installation flexibility, reliability, maximum performance, and easy accessibility for maintenance and repair.

Flexible hose improves alignment for customer connections, and all seawater connections are reinforced with stainless-steel for added strength. Thermal expansion valves optimize performance over a wide range of conditions, while a hot-gas bypass valve maintains heating performance in cold seawater and helps prevent water freezing in the heat exchanger. With heating performance effective in cold seawater temperatures as low as 38°F (3.5°C), the need for separate fossil fuel or electric water heaters is eliminated in most applications.

The MTD is available in capacities of 24,000 to 120,000 BTU/hr (2 to 10 tons), and you can use multiple modules in any combination to achieve the total desired capacity. Custom frame and water-manifold installation for multiple units are also available. A reverse-cycle unit, the MTD provides reliable cooling and heating.

Each MTD unit has two sub-modules. This lets you rotate a sub-module to achieve more convenient water-connection locations or compressor access. The sub-modules can even be separated for remote mounting when space is limited. Sub-module changes can be handled in the field or special ordered from the factory.

The MTD has many built-in protection devices. A wire harness with polarized plug is included for easy electrical connections.

MTD units are available with several different compressors to suit a variety of power systems, including: 230V/60Hz/1Ph, 220V/50Hz/1Ph, 230V/60Hz/3Ph, 380V/50Hz/3Ph, and 460V/60Hz/3Ph.

Optional Variable Frequency Drives (VFDs) are available, which eliminate start-up power surge and run the unit at full-capacity 60Hz even with 50Hz input. The VFD requires a 3-phase tempering unit, but can operate on 1- or 3-phase input power.

Key Benefits

- Engineered to maximize the performance of R-410A, an environmentally safe refrigerant.
- Modular design for installation flexibility.
- Reverse-cycle heating.
- Scroll compressors standard.
- Larger drain fittings for faster condensate drainage.
- Stainless-steel reinforced seawater connections.
- Flexible hose improves connection alignment.
- Removable seawater manifolds allow cleaning of condenser tubing.
- Integrated loop-water strainer and flow switch.
- Oversized heat exchangers for loop temperatures of 40°F (4.4°C) in cooling and 120°F (49°C) in heating.
- Thermal expansion valve for optimal performance over a range of conditions.
- Hot-gas bypass valve maintains heating performance in cold seawater and helps prevent water freezing in the heat exchanger.



by Dometic GROUP

